HEXIS'O

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878
Issue date: 01/10/2013 Revision date: 05/01/2026 Supersedes version of: 16/02/2024 Version: 7.2

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form : Mixture
Name (SDS) : HEXIS'O
UFI : JGJW-S0M6-N00Y-RCSR
Product code : HEXISO
Type of product : Detergent

1.2. Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses

Main use category : Professional use,Industrial use

1.3. Details of the supplier of the safety data sheet

Société HEXIS
Z.I. HORIZONS SUD CS 970003
34118 FRONTIGNAN CEDEX
France
T 0 33 04 67 18 66 80, F 0 33 04 67 48 38 79

1.4. Emergency telephone number

Emergency number : 01 45 42 59 59 (ORFILA)

Country/Area	Organisation	Emergency number
Australia	NSW Poisons Information Centre. The Children's Hospital at Westmead. Locked Bag 4001 NSW 2145.	13 11 26
Ireland	National Poisons Information Centre. Beaumont Hospital. PO Box 1297. Beaumont Road 9 Dublin.	+353 1 809 2566 (Healthcare professionals-24/7) +353 1 809 2166 (public, 8am - 10pm, 7/7)
Malta	Medicines & Poisons Info Office. Mater Dei Hospital. Msida MSD 2090 Msida.	112 +356 2545 6508
United Kingdom	National Poisons Information Service (Birmingham Centre). City Hospital. Dudley Road B18 7QH.	0344 892 0111 Only for healthcare professionals

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Flammable liquids, Category 2 H225
Serious eye damage/eye irritation, Category 2 H319
Specific target organ toxicity – Single exposure, Category 3, Narcosis H336
Full text of H- and EUH-statements: see section 16

Adverse physicochemical, human health and environmental effects

Highly flammable liquid and vapour. May cause drowsiness or dizziness. Causes serious eye irritation.

2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP) :



GHS02 GHS07

Signal word (CLP) : Danger

Contains : propan-2-ol

Hazard statements (CLP) : H225 - Highly flammable liquid and vapour.
H319 - Causes serious eye irritation.
H336 - May cause drowsiness or dizziness.

Precautionary statements (CLP) : P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P261 - Avoid breathing spray, mist, fume, gas, dust, vapours.
P280 - Wear protective gloves, protective clothing, eye protection, face protection.
P312 - Call a POISON CENTER, a doctor if you feel unwell.
P337+P313 - If eye irritation persists: Get medical advice/attention.

2.3. Other hazards

Contains no PBT and/or vPvB substances ≥ 0.1% assessed in accordance with REACH Annex XIII

The mixture does not contain substance(s) included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or substance(s) are not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at a concentration equal to or greater than 0,1 %

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
propan-2-ol substance with national workplace exposure limit(s) (DE, FR, NL)	CAS-No.: 67-63-0 EC-No.: 200-661-7 EC Index-No.: 603-117-00-0 REACH-no: 01-2119457558-25	50-100	Flam. Liq. 2, H225 Eye Irrit. 2, H319 STOT SE 3, H336

Full text of H- and EUH-statements: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures general : Call a poison center or a doctor if you feel unwell.

First-aid measures after inhalation : Remove person to fresh air and keep comfortable for breathing.

First-aid measures after skin contact : Rinse skin with water/shower. Take off immediately all contaminated clothing.

First-aid measures after eye contact : Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.

First-aid measures after ingestion : Call a poison center or a doctor if you feel unwell.

Self protection of the first-aider : First-aiders should pay attention to their own protection and use the recommended personal protective equipment (see section 8).

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects : May cause drowsiness or dizziness.

Symptoms/effects after inhalation	:	None under normal conditions.
Symptoms/effects after skin contact	:	None under normal conditions.
Symptoms/effects after eye contact	:	Eye irritation.
Symptoms/effects after ingestion	:	None under normal conditions.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media	:	Water spray. Dry powder. Foam. Carbon dioxide.
Unsuitable extinguishing media	:	Do not use a heavy water stream.

5.2. Special hazards arising from the substance or mixture

Fire hazard	:	Highly flammable liquid and vapour.
Explosion hazard	:	May form flammable/explosive vapour-air mixture.
Hazardous decomposition products in case of fire	:	Carbon monoxide. Carbon dioxide.

5.3. Advice for firefighters

Firefighting instructions	:	Fight fire from safe distance and protected location. Do not enter fire area without proper protective equipment, including respiratory protection. Exercise caution when fighting any chemical fire. Use water spray or fog for cooling exposed containers. Prevent fire fighting water from entering the environment.
Protection during firefighting	:	Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures	:	Stop leak if safe to do so. Notify authorities if product enters sewers or public waters. Absorb spillage to prevent material damage. Evacuate unnecessary personnel. Do not handle until all safety precautions have been read and understood. Wear recommended personal protective equipment.

For non-emergency personnel

Protective equipment	:	Wear recommended personal protective equipment.
Emergency procedures	:	Ventilate spillage area. No open flames, no sparks, and no smoking. Avoid breathing spray, mist, fume, gas, dust, vapours. Avoid contact with skin and eyes.

For emergency responders

Protective equipment	:	Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".
Emergency procedures	:	Evacuate unnecessary personnel. Stop leak if safe to do so.

6.2. Environmental precautions

Avoid release to the environment. Prevent entry to sewers and public waters. Notify authorities if product enters sewers or public waters.

6.3. Methods and material for containment and cleaning up

For containment	:	Absorb spilled material with sand or earth. Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams. Stop leak without risks if possible.
Methods for cleaning up	:	Take up liquid spill into absorbent material. Notify authorities if product enters sewers or public waters.
Other information	:	Dispose of materials or solid residues at an authorized site.

6.4. Reference to other sections

For further information refer to section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Additional hazards when processed	:	Flammable vapours may accumulate in the container. Handle empty containers with care because residual vapours are flammable.
Precautions for safe handling	:	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Ground/bond container and receiving equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Flammable vapours may accumulate in the container. Use explosion-proof equipment. Wear personal protective equipment. Use only outdoors or in a well-ventilated area. Avoid breathing spray, mist, fume, gas, dust, vapours. Avoid contact with skin and eyes.
Hygiene measures	:	Do not eat, drink or smoke when using this product. Always wash hands after handling the product. Keep away from food, drink and animal feeding stuffs.

7.2. Conditions for safe storage, including any incompatibilities

Technical measures	:	Use explosion-proof ventilating, lighting, electrical equipment. Proper grounding procedures to avoid static electricity should be followed. Ground/bond container and receiving equipment.
Storage conditions	:	Store in a well-ventilated place. Keep cool. Keep container tightly closed. Store locked up. Protect from freezing. Protect from sunlight.
Incompatible products	:	Amines. chlorinated derivatives. Strong acids. Oxidizing agent. Strong bases.
Incompatible materials	:	Heat sources. Direct sunlight. Sources of ignition.
Storage temperature	:	5 – 30 °C
Packaging materials	:	Mild steel. stainless steel. glass. Coated steels. Always store product in container of same material as original container.

7.3. Specific end use(s)

No additional information available

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

National occupational exposure and biological limit values

propan-2-ol (67-63-0)	
France - Occupational Exposure Limits	
Local name	Alcool isopropylique
VLEP CT (OEL STEL)	980 mg/m³
	400 ppm
Remark	Valeurs recommandées/admises
Regulatory reference	Circulaire du Ministère du travail (réf.: INRS ED 6443, 2022; Outil65)
Germany - Occupational Exposure Limits (TRGS 900)	
AGW (OEL TWA)	500 mg/m³
AGW (OEL C)	1000 mg/m³
Netherlands - Occupational Exposure Limits	
TGG-8u (OEL TWA)	650 mg/m³
TGG-15min (OEL STEL)	0 mg/m³

8.2. Exposure controls

Appropriate engineering controls

Appropriate engineering controls:
Ensure good ventilation of the work station.

Personal protection equipment

Personal protective equipment:
Wear recommended personal protective equipment.
Personal protective equipment symbol(s):



Eye and face protection

Eye protection:
Safety glasses

Eye protection			
Type	**Field of application**	**Characteristics**	**Standard**
Safety glasses	Droplet	With side shields	EN 166

Skin protection

Skin and body protection:
Wear suitable protective clothing

Hand protection:
Wear suitable gloves resistant to chemical penetration. Since the product consists of several substances, the durability of the glove material cannot be estimated and needs to be tested before use. Please follow the instructions related to the permeability and the penetration time provided by the manufacturer. Choosing the proper glove is a decision that depends not only on the type of material, but also on other quality features, which differ for each manufacturer. Protective gloves

Respiratory protection

Respiratory protection:
In case of insufficient ventilation, wear suitable respiratory equipment

Respiratory protection			
Device	**Filter type**	**Condition**	**Standard**
Gas filters, Gas mask, Aerosol mask	Type A - High-boiling (>65 °C) organic compounds, Type P2	Protection for Liquid particles, Vapour protection	EN 136, EN 140, EN 405, EN 143, EN 14387, EN 149

Environmental exposure controls

Environmental exposure controls:
Avoid release to the environment.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	:	Liquid
Colour	:	Yellow.
Odour	:	Not available
Odour threshold	:	Not available
Melting point	:	Not applicable
Freezing point	:	Not available
Boiling point	:	82 °C

Flammability	:	Highly flammable liquid and vapour.
Lower explosion limit	:	Not available
Upper explosion limit	:	Not available
Flash point	:	12 °C
Auto-ignition temperature	:	Not available
Decomposition temperature	:	Not available
pH	:	8
pH solution concentration	:	10 %
Viscosity, kinematic	:	Not available
Solubility	:	In water, material soluble.
Partition coefficient n-octanol/water (Log Kow)	:	Not available
Vapour pressure	:	4,2 kPa 20°C
Vapour pressure at 50°C	:	Not available
Density	:	Not available
Relative density	:	0,79 +/-0.03
Relative vapour density at 20°C	:	Not available
Particle characteristics	:	Not applicable

9.2. Other information

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

Highly flammable liquid and vapour.

10.2. Chemical stability

May form flammable/explosive vapour-air mixture.

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

10.4. Conditions to avoid

Avoid contact with hot surfaces. Heat. No flames, no sparks. Eliminate all sources of ignition. None under recommended storage and handling conditions (see section 7). Extremely high or low temperatures. Direct sunlight. gel.

10.5. Incompatible materials

amines. Chlorine. Strong acids. Oxidizing agent. Strong bases.

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity (oral)	:	Not classified (Based on available data, the classification criteria are not met)
Acute toxicity (dermal)	:	Not classified (Based on available data, the classification criteria are not met)
Acute toxicity (inhalation)	:	Not classified (Based on available data, the classification criteria are not met)

propan-2-ol (67-63-0)	
LD50 oral rat	5840 mg/kg
LD50 oral	4396 mg/kg bodyweight
LD50 dermal rabbit	13900 mg/kg
LD50 dermal	12800 mg/kg bodyweight

propan-2-ol (67-63-0)	
LC50 Inhalation - Rat (Dust/Mist)	46600 mg/l

Skin corrosion/irritation : Not classified (Based on available data, the classification criteria are not met)
pH: 8

Serious eye damage/irritation : Causes serious eye irritation.
pH: 8

Respiratory or skin sensitisation : Not classified (Based on available data, the classification criteria are not met)

Germ cell mutagenicity : Not classified (Based on available data, the classification criteria are not met)

Carcinogenicity : Not classified (Based on available data, the classification criteria are not met)

Reproductive toxicity : Not classified (Based on available data, the classification criteria are not met)

STOT-single exposure : May cause drowsiness or dizziness.

propan-2-ol (67-63-0)	
STOT-single exposure	May cause drowsiness or dizziness.

STOT-repeated exposure : Not classified (Based on available data, the classification criteria are not met)

Aspiration hazard : Not classified (Based on available data, the classification criteria are not met)

propan-2-ol (67-63-0)	
Viscosity, kinematic	3,185 mm²/s

11.2. Information on other hazards

No additional information available

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general : The product is not considered harmful to aquatic organisms nor to cause long-term adverse effects in the environment. Do not discharge into drains or the environment.

Hazardous to the aquatic environment, short–term (acute) : Not classified (Based on available data, the classification criteria are not met)

Hazardous to the aquatic environment, long–term (chronic) : Not classified (Based on available data, the classification criteria are not met)

Additional information : Based on available data, the classification criteria are not met.

propan-2-ol (67-63-0)	
LC50 - Fish [1]	9640 mg/l
EC50 - Other aquatic organisms [1]	13299 mg/l waterflea
EC50 - Other aquatic organisms [2]	> 1000 mg/l

12.2. Persistence and degradability

HEXIS'O	
Persistence and degradability	Not rapidly degradable

propan-2-ol (67-63-0)	
Persistence and degradability	Readily biodegradable.
Biochemical oxygen demand (BOD)	1,171 g O_2/g substance
Chemical oxygen demand (COD)	2,294 g O_2/g substance
Biodegradation	> 70 % 28 jours

12.3. Bioaccumulative potential

propan-2-ol (67-63-0)	
Partition coefficient n-octanol/water (Log Pow)	0,05

12.4. Mobility in soil

No additional information available

12.5. Results of PBT and vPvB assessment

No additional information available

12.6. Endocrine disrupting properties

No additional information available

12.7. Other adverse effects

No additional information available

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Regional waste regulation : Disposal must be done according to official regulations.

Waste treatment methods : Dispose of contents/container in accordance with licensed collector's sorting instructions.

Sewage disposal recommendations : Disposal must be done according to official regulations.

Product/Packaging disposal recommendations : Disposal must be done according to official regulations. Dispose in a safe manner in accordance with local/national regulations. Do not discharge into drains or the environment.

Additional information : Handle empty containers with care because residual vapours are flammable. Flammable vapours may accumulate in the container. Do not re-use empty containers.

Ecological waste information : The waste of the product should be considered as hazardous as the product itself, with the likelihood of impacting the environment in the same way. Consider the handling and disposal of the waste as defined by the product itself. Do not discharge into drains or the environment.

HP Code : HP3 - "Flammable:"
– flammable liquid waste: liquid waste having a flash point below 60 °C or waste gas oil, diesel and light heating oils having a flash point > 55 °C and ≤ 75 °C;
– flammable pyrophoric liquid and solid waste: solid or liquid waste which, even in small quantities, is liable to ignite within five minutes after coming into contact with air;
– flammable solid waste: solid waste which is readily combustible or may cause or contribute to fire through friction;
– flammable gaseous waste: gaseous waste which is flammable in air at 20 °C and a standard pressure of 101.3 kPa;
– water reactive waste: waste which, in contact with water, emits flammable gases in dangerous quantities;
– other flammable waste: flammable aerosols, flammable self-heating waste, flammable organic peroxides and flammable self-reactive waste.
HP4 - "Irritant – skin irritation and eye damage:" waste which on application can cause skin irritation or damage to the eye.

SECTION 14: Transport information

In accordance with ADR / IMDG / IATA / ADN / RID


ADR	IMDG	IATA	ADN	RID
14.1. UN number or ID number				
UN 1219	UN 1219	Not applicable	UN 1219	UN 1219

ADR	IMDG	IATA	ADN	RID
14.2. UN proper shipping name				
ISOPROPANOL (ISOPROPYL ALCOHOL)	ISOPROPANOL (ISOPROPYL ALCOHOL)	Not applicable	ISOPROPANOL (ISOPROPYL ALCOHOL)	ISOPROPANOL (ISOPROPYL ALCOHOL)
Transport document description				
UN 1219 ISOPROPANOL (ISOPROPYL ALCOHOL), 3, II, (D/E)	UN 1219 ISOPROPANOL (ISOPROPYL ALCOHOL), 3, II (12°C c.c.)	Not applicable	UN 1219 ISOPROPANOL (ISOPROPYL ALCOHOL), 3, II	UN 1219 ISOPROPANOL (ISOPROPYL ALCOHOL), 3, II
14.3. Transport hazard class(es)				
3	3	Not applicable	3	3
		Not applicable		
14.4. Packing group				
II	II	Not applicable	II	II
14.5. Environmental hazards				
Dangerous for the environment: No	Dangerous for the environment: No Marine pollutant: No EmS-No. (Fire): F-E EmS-No. (Spillage): S-D	Not applicable	Dangerous for the environment: No	Dangerous for the environment: No
No supplementary information available				

14.6. Special precautions for user

Overland transport

Classification code (ADR) : F1
Special provisions (ADR) : 601
Limited quantities (ADR) : 1l
Excepted quantities (ADR) : E2
Packing instructions (ADR) : P001, IBC02, R001
Mixed packing provisions (ADR) : MP19
Portable tank and bulk container instructions (ADR) : T4
Portable tank and bulk container special provisions (ADR) : TP1
Tank code (ADR) : LGBF
Vehicle for tank carriage : FL
Transport category (ADR) : 2
Special provisions for carriage - Operation (ADR) : S2, S20
Hazard identification number (Kemler No.) : 33
Orange plates :



Tunnel restriction code (ADR) : D/E
EAC code : •2YE

Transport by sea

Limited quantities (IMDG) : 1 L
Excepted quantities (IMDG) : E2
Packing instructions (IMDG) : P001
IBC packing instructions (IMDG) : IBC02
Tank instructions (IMDG) : T4
Tank special provisions (IMDG) : TP1

Stowage category (IMDG)	:	B
Flash point (IMDG)	:	12°C c.c.
Properties and observations (IMDG)	:	Colourless, mobile liquid. Flashpoint: 12°C c.c. Explosive limits: 2% to 12%. Miscible with water.

Air transport
Not applicable

Inland waterway transport

Classification code (ADN)	:	F1
Special provisions (ADN)	:	601
Limited quantities (ADN)	:	1 L
Excepted quantities (ADN)	:	E2
Carriage permitted (ADN)	:	T
Equipment required (ADN)	:	PP, EX, A
Ventilation (ADN)	:	VE01
Number of blue cones/lights (ADN)	:	1

Rail transport

Classification code (RID)	:	F1
Special provisions (RID)	:	601
Limited quantities (RID)	:	1L
Excepted quantities (RID)	:	E2
Packing instructions (RID)	:	P001, IBC02, R001
Mixed packing provisions (RID)	:	MP19
Portable tank and bulk container instructions (RID)	:	T4
Portable tank and bulk container special provisions (RID)	:	TP1
Tank codes for RID tanks (RID)	:	LGBF
Transport category (RID)	:	2
Colis express (express parcels) (RID)	:	CE7
Hazard identification number (RID)	:	33

14.7. Maritime transport in bulk according to IMO instruments

Not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU-Regulations

REACH Annex XVII (Restriction List)

EU restriction list (REACH Annex XVII)

Reference code	Applicable on	Entry title or description
3(a)	HEXIS'O ; propan-2-ol	Substances or mixtures fulfilling the criteria for any of the following hazard classes or categories set out in Annex I to Regulation (EC) No 1272/2008: Hazard classes 2.1 to 2.4, 2.6 and 2.7, 2.8 types A and B, 2.9, 2.10, 2.12, 2.13 categories 1 and 2, 2.14 categories 1 and 2, 2.15 types A to F
3(b)	HEXIS'O ; propan-2-ol	Substances or mixtures fulfilling the criteria for any of the following hazard classes or categories set out in Annex I to Regulation (EC) No 1272/2008: Hazard classes 3.1 to 3.6, 3.7 adverse effects on sexual function and fertility or on development, 3.8 effects other than narcotic effects, 3.9 and 3.10

REACH Annex XIV (Authorisation List)
Contains no substance(s) listed on REACH Annex XIV (Authorisation List)

REACH Candidate List (SVHC)
Contains no substance(s) listed on the REACH Candidate List

PIC Regulation (Prior Informed Consent)

Contains no substance(s) listed on the PIC list (Regulation EU 649/2012 concerning the export and import of hazardous chemicals)

POP Regulation (Persistent Organic Pollutants)

Contains no substance(s) listed on the POP list (Regulation EU 2019/1021 on persistent organic pollutants)

Ozone Regulation (2024/590)

Not listed on the Ozone Depletion list (Regulation EU 2024/590)
Contains no substance(s) listed on the Ozone Depletion list (Regulation EU 2024/590 on substances that deplete the ozone layer)

Council Regulation (EC) for the control of dual-use items

Contains no substance subject to the COUNCIL REGULATION (EC) for the control of dual-use items

Detergent Regulation (EC 648/2004)

Contains no ingredient(s) required to be listed according to the Detergent Regulation (648/2004).

Explosives Precursors Regulation (EU 2019/1148)

Contains no substance(s) listed on the Explosives Precursors list (Regulation EU 2019/1148 on the marketing and use of explosives precursors)

Drug Precursors Regulation (EC 273/2004)

Contains no substance(s) listed on the Drug Precursors list (Regulation EC 273/2004 on the manufacture and the placing on market of certain substances used in the illicit manufacture of narcotic drugs and psychotropic substances)

National regulations

Denmark

Class for fire hazard	:	Class I-1
Store unit	:	1 liter
Classification remarks	:	F <Flam. Liq. 2>; Emergency management guidelines for the storage of flammable liquids must be followed
Danish National Regulations	:	Young people below the age of 18 years are not allowed to use the product Pregnant/breastfeeding women working with the product must not be in direct contact with it. If an employee is pregnant or breastfeeding and the person in question uses or is exposed to this product at work, the employer must always carry out a risk assessment of the work. The assessment must both deal with the dangerousness of the impact and its strength and duration. The employer's decision that a pregnant or lactating woman can perform a specific work task must therefore be made in the context of her specific working conditions. See also WEA-Guideline A.1.8-7 on the working environment of pregnant and breastfeeding workers. Listed or contains substance(s) on the Denmark - Indicative list of organic solvents present in Annex 3.4.1 of the WEA Guidance C.0.1-1: Isopropyl alcohol (2005) (67-63-0)

Finland

France

Occupational diseases	
Code	Description
RG 84	Conditions caused by liquid organic solvents for professional use: saturated or unsaturated aliphatic or cyclic liquid hydrocarbons and mixtures thereof; liquid halogenated hydrocarbons; nitrated derivatives of aliphatic hydrocarbons; alcohols; glycols, glycol ethers; ketones; aldehydes; aliphatic and cyclic ethers, including tetrahydrofuran; esters; dimethylformamide and dimethylacetamine; acetonitrile and propionitrile; pyridine; dimethylsulfone and dimethylsulfoxide

Germany

Water hazard class (WGK)	:	WGK 1, Slightly hazardous to water (Classification according to AwSV, Annex 1).

Netherlands

ABM category	:	B(4) - low hazard for aquatic organisms
SZW-lijst van kankerverwekkende stoffen	:	None of the components are listed
SZW-lijst van mutagene stoffen	:	None of the components are listed
SZW-lijst van reprotoxische stoffen – Borstvoeding	:	None of the components are listed
SZW-lijst van reprotoxische stoffen – Vruchtbaarheid	:	None of the components are listed

SZW-lijst van reprotoxische stoffen – Ontwikkeling : None of the components are listed

Poland

Polish National Regulations : Act of 25 February 2011 on chemical substances and their mixtures (J. o L. No. 63, item 322 as amended; consolidated text J. o L. 2019, item 1225).
Act of 14 December 2012 on waste (J. o L. 2013, item 322 as amended; consolidated text J. o L. 2020, item 797).
The announcement of Marshal of the Sejm of the Republic of Poland dated 19 October 2016 concerning the consolidated text announcement of the decree on the management of packaging and packaging waste (J. o L. 2016, item 1863 as amended).
Decree of the Minister of Environment of 14 December 2014 on the catalogue of waste (J. o L. 2014, item 1923).
Act of 19 August 2011 on the Carriage of Dangerous Goods (J. o L. 2011 No. 227, item 1367 as amended; consolidated text J. o L. 2020, item 154).
Regulation of the Minister of Family, Labour and Social Policy of 12 June 2018 on the highest permissible concentration and intensity of noxious agents for health at work environment (J. o L. item 1286 as amended).
The announcement of Minister of Health dated 9 September 2016 concerning the consolidated text announcement of the decree of the Minister of Health of 30 December 2004 on health and safety at work related to exposure to chemical agents at work (J. o L. of 16 September 2016, item 1488)
Regulation of the Minister of Health of 2 February 2011 on tests and measurements of the noxious agents for health at work environment (J. o L. No. 33, item 166 as amended).
Regulation of the Minister of Environment of 9 December 2003 on particularly hazardous substances to the environment (J. o L. No. 217, item 2141).
ADR Agreement: Government Statement of 13 March 2023 on the entry into force of amendments to Annexes A and B to the Agreement concerning the International Carriage of Dangerous Goods by Road (ADR), signed in Geneva on 30 September 1957 (J. o. L. 2023, item 891)
Regulation of the Minister of Health of 25 August 2015 on the method of marking places, pipelines, and containers and tanks used for storing or containing hazardous substances or hazardous mixtures (J.o.L. 2015, item 1368 as amended)

15.2. Chemical safety assessment

No chemical safety assessment has been carried out

SECTION 16: Other information

Indication of changes

Section	Changed item	Comments
	Additional information	**Added**
	Supersedes	**Modified**
	Revision date	**Modified**
1.1	UFI on SDS 1.1	**Modified**
1.2	Main use category	**Modified**
4	Self protection of the first-aider	**Added**
4.2	Symptoms/effects after inhalation	**Added**
4.2	Symptoms/effects after ingestion	**Added**
4.2	Symptoms/effects after skin contact	**Added**
5.3	Firefighting instructions	**Modified**
6.1	General measures	**Modified**
6.1	Emergency procedures	**Added**
6.1	Protective equipment	**Added**

Indication of changes		
Section	**Changed item**	**Comments**
6.3	For containment	**Added**
7.2	Packaging materials	**Modified**
7.2	Incompatible materials	**Modified**
7.2	Incompatible products	**Modified**
7.2	Storage conditions	**Modified**
8.2	Personal protective equipment	**Added**
8.2	Hand protection	**Modified**
9	Flammability (solid, gas)	**Modified**
10.4	Conditions to avoid	**Modified**
10.5	Incompatible materials	**Modified**
12.1	Ecology - general	**Modified**
13.1	Ecology - waste materials	**Modified**
13.1	Product/Packaging disposal recommendations	**Modified**
13.1	Regional waste regulation	**Added**
13.1	Sewage disposal recommendations	**Added**
13.1	Additional information	**Modified**
15.1	REACH Annex XVII	**Modified**
16	Abbreviations and acronyms	**Modified**

Abbreviations and acronyms:	
ACGIH	American Conference of Governmental Industrial Hygienists
ADN	European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways
ADR	European Agreement concerning the International Carriage of Dangerous Goods by Road
ATE	Acute Toxicity Estimate
BCF	Bioconcentration factor
BLV	Biological limit value
BOD	Biochemical oxygen demand (BOD)
CAS-No.	Chemical Abstracts Service number
CLP	Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008
COD	Chemical oxygen demand (COD)
CSA	Chemical safety assessment
DMEL	Derived Minimal Effect level
DNEL	Derived-No Effect Level
EC-No.	European Community number
EC50	Median effective concentration
ED	Endocrine disruptor
EN	European Standard

Abbreviations and acronyms:	
EWC	European waste catalogue
IARC	International Agency for Research on Cancer
IATA	International Air Transport Association
IMDG	International Maritime Dangerous Goods
LC50	Median lethal concentration
LD50	Median lethal dose
LOAEL	Lowest Observed Adverse Effect Level
Log Kow	Partition coefficient n-octanol/water (Log Kow)
Log Pow	Partition coefficient n-octanol/water (Log Pow)
MAK	maximum workplace concentration
NOAEC	No-Observed Adverse Effect Concentration
NOAEL	No-Observed Adverse Effect Level
NOEC	No-Observed Effect Concentration
N.O.S.	Not Otherwise Specified
OECD	Organisation for Economic Co-operation and Development
OEL	Occupational Exposure Limit
OSHA	Occupational Safety Health Administration
PBT	Persistent Bioaccumulative Toxic
PNEC	Predicted No-Effect Concentration
PPE	Personal protection equipment
RID	Regulations concerning the International Carriage of Dangerous Goods by Rail
SDS	Safety Data Sheet
STP	Sewage treatment plant
TF	Technical function
ThOD	Theoretical oxygen demand (ThOD)
TLM	Median Tolerance Limit
TWA	Time Weighted Average
VOC	Volatile Organic Compounds
vPvB	Very Persistent and Very Bioaccumulative
UFI	Unique Formula Identifier

Full text of H- and EUH-statements:	
Eye Irrit. 2	Serious eye damage/eye irritation, Category 2
Flam. Liq. 2	Flammable liquids, Category 2
STOT SE 3	Specific target organ toxicity – Single exposure, Category 3, Narcosis
H225	Highly flammable liquid and vapour.
H319	Causes serious eye irritation.
H336	May cause drowsiness or dizziness.

Classification and procedure used to derive the classification for mixtures according to Regulation (EC) 1272/2008 [CLP]:		
Flam. Liq. 2	H225	On basis of test data
Eye Irrit. 2	H319	Calculation method
STOT SE 3	H336	Calculation method

Safety Data Sheet (SDS), EU

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.