# **Metamark MM-CC Colour Change**

**Cylinder Cast Wrapping Film** 



### **Metamark Colour Change Benefits**

Metamark Colour Change film is a proven and highly effective full colour branding vehicle wrap solution for use on fleet, commercial and taxi applications. The Apex adhesive ensures minimal residue on removal, to restore the vehicle to its base colour, and so optimising the total project production time for each vehicle. Metamark Colour Change offers high abrasion resistance and paint protection to preserve the market resale value of the vehicle at the end of the contract.

#### **Product Description**

The 100 micron film offers high opacity and resistance to elongation colour fade during the wrapping process. The pigments in the film give long term colour stability, providing a durable finish. It is supplied with MetaScape air release system to allow quick and easy application.

#### **Colour Range**

MM-CC is available in a range of standard colours ex-stock, and is alternatively offered to colour match for minimum quantities, for specific branding opportunities.

## **Application**

- Refer to 'MM-CC' application guidelines to ensure correct installation.
- Use a dry application method.
- Use gentle heat to allow conformability. Do not overstretch as this will cause the application to fail
- After application 'superheat' the film into recesses at 90-95°C.
- Yellow and Tangerine are not suitable for darker vehicles due to low opacity. The user should determine suitability for the vehicle.
- Also suitable for plotter use also for contour and vinyl lettering.
- It is advised to contact insurers when changing the colour of the vehicle.

Face Film		Finishes	
Face Film: Gauge: Adhesive	Cylinder Cast 100 micron nominal	Finishes	Available in a range of standard colours ex-stock, also available supplied to colour match. Please contact us for more details.
Туре	'MetaScape' permanent solvent-based	Roll Presentation	
Weight Adhesion to glass 20 mins Adhesion to glass 24 hour	acrylic with air channels 27gsm nominal 15N/25mm nominal 20N/25mm nominal	Roll sizes and net weights Presentation	1520mm x 50m 22kg Face film outwards, on a 76mm core.
Perceived tack Shear strength	Medium Medium to high	Durability	
Application temperature Service temperature	+10°C to +60°C -30°C to +110°C	Shelf Life External weathering	2 years 8 years for black and white, 7 years for colours and 5 years for metallic; in
Release Liner			vertical exposure under northern
Print Weight Type	'MetaScape' print 135 gsm nominal Structured layflat kraft with PE coating	Fire Rating Dimensional Stability Regulations Chemical Resistance	European conditions. Self Extinguishing. <0.5% (48h at 70°C on aluminium) REACH compliant Resistant to mineral oils, fats and fuels, aliphatic solvents, mild acids, salt and alkali for e.g. diesel oil, gasoline, paraffin, hydraulic oil, antifreeze, soap suds etc.

Warranty: Metamark (UK) Limited warrants to its customers that completed decorative markings which utilise Metamark SignVinyl will remain in good condition without excessive fading or colour degradation for the specified life time of each material when correctly stored and applied in accordance with procedures outlined in the technical literature. If within the specified years of normal use Metamark SignVinyl becomes ineffective for its intended use, then Metamark will provide sufficient material to produce a new replacement marking, and will also, at its own discretion, contribute an allowance towards the costs involved in replacing the graphics.

Please Note: The above data is given in good faith to provide an indication of the performance of the product. Purchasers should consider the suitability of each product for its intended use and the purchaser assumes all risks in connection with such use. Seller shall not be liable for damages in excess of the purchase price of the product nor for incidental nor consequential loss.

## Metamark (UK) Limited